

SYNTULA 5W30 C2 PSA

SYNTULA 5W30 C2 PSA this is a full synthetic high-performance engine oil with low viscosity, specifically developed to provide the highest fuel economy and lowest CO2 emissions.

SYNTULA 5W30 C2 PSA meets the following specifications:

API SN/CF
ACEA C2-12
PSA Oil meeting specification B71 2290
RENAULT RN 0700
FIAT 9.55535-s1

APPLICATIONS

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

FEATURES

After treatment protection : full after treatment system protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO2 emissions

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
SAE-classe			5W30
Density at 15°C	D4052	kg/m3	0,856
Viscosity at 40°C	D445	cSt	56
Viscosity at 100°C	D445	cSt	10,2
Viscosity at -30°C	D5293	cP	5500
Viscosity index	D2270		168
Flash point COC	D92	°C	235
Pour point	D6892	°C	-39
TBN	D2896	gKOH/kg	7,5
Sulphated ash	D874	massa %	0,79

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: **ARVA106**