

SYNTULA FM 5W30

SYNTULA FM 5W30 is a synthetic, fuel economy "MID SAPS" motor oil especially designed for requirements of the Ford specification WSS-M2C-913-C. It is characterized by highly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications and is suitable for diesel particulate filters.

SYNTULA FM 5W30 meets the following specifications:

API SL/CF
ACEA A1/B1-08, A5/B5-08
FORD WSS-M2C-913-C
FORD WSS-M2C-913-D
RENAULT RN0700
JAGUAR / LAND ROVER STJR.03.5003
IVECO 18-1811

APPLICATIONS :

SYNTULA FM 5W30 is especially designed for the newest generation FORD engines, gasoline engines and diesel engines with diesel particulate filters (DPF), This oil cannot be used for engines equipped with pump-injectors. (Ford Galaxy I & II and Ford KA (gasoline & diesel from 2009)).

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average result |
|--------------------|--------|---------|----------------|
| SAE-classe | | | 5W30 |
| Density at 15°C | D4052 | kg/m3 | 0,852 |
| Viscosity at 40°C | D445 | cSt | 52 |
| Viscosity at 100°C | D445 | cSt | 9.6 |
| Viscosity at -30°C | D5293 | cP | 4000 |
| Viscosity index | D2270 | | 173 |
| Flash point COC | D92 | °C | 218 |
| Pour point | D6892 | °C | -39 |
| TBN | D2896 | gKOH/kg | 10.1 |
| Sulphated ash | D874 | massa % | 1.09 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: **ARVA105**