

ULTIM RACE X 10W60

A fully synthetic ester engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

PERFORMANCE LEVEL

- ACEA A3/B4-12
- API SN/CF

APPLICATIONS

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density at 15°C		kg/l	0,867
Viscosity at -25°C		mPa.s	6040
Viscosity at 40°C	ASTM D 445	mm ² /s	155.10
Viscosity at 100°C	ASTM D 445	mm ² /s	24.1
Viscosity index	ASTM D 2270		189
Pour Point	ASTM D 97	°C	-48
Total Base Number	ASTM D 2896	mgKOH/g	10.5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV123