

## ULTIM SPORT 5W30

A universal, ester fortified, synthetic motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index.

With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

**ULTIM SPORT 5W30** meets the following specifications:

MB 229.51/229.52  
VW 502.00/505.00/505.01  
BMW Longlife-04  
Dexos 2  
ACEA C3-12  
API SN

### APPLICATIONS

This is a universal, ester fortified, synthetic motor oil.

This Oil is specially developed for passenger car engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging with or without DPF (Diesel particulate filter).

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density at 15°C		kg/l	0,859
Viscosity at -250°C		mPa.s	3750
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	56
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	10
Viscosity index	ASTM D 2270		181
Pour Point	ASTM D 97	°C	-42
Total Base Number	ASTM D 2896	mgKOH/g	7,2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

ART : ARV120