

## SYNTULA 0W20 V

**SYNTULA 0W20 V** This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the gasoline and diesel direct injection Volvo Engine Architecture (VEA) engines. This VOLVO VCC RBS0-2AE specification demands high oxidation stability to ensure long oil drain intervals of up to 30000 km. There is a fuel economy benefit over a reference oil of 3,4 %.

**SYNTULA 0W20 V** meets the following specifications:

- ACEA A1/B1-12
- Volvo VCC RBS0-2AE

### FEATURES

Total engine protection : performance in keeping the engine clean.

Fuel economy : superior fuel economy and CO2 reduction.

Cold start : excellent fluidity at low temperature.

### APPLICATIONS :

This product was primarily developed for mandatory use in the gasoline and diesel direct injection Volvo Engine Architecture (VEA) engines. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA A1/B1 performance, thus providing a multi vehicle oil application. It provides an extremely quick and stable lubricant film at the cold start at low temperatures and offers high thermal stability under heavy duty operating conditions.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W20
Density at 15°C	D4052	kg/m <sup>3</sup>	844
Viscosity at 40°C	D445	cSt	48
Viscosity at 100°C	D445	cSt	9.1
CCS Viscosity at -25°C	D5293	cP	5920
Viscosity index	D2270		171
Flash point COC	D92	°C	225
Pour point	D6892	°C	-48
TBN	D2896	gKOH/kg	7.8

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.*

Product code: ARV138