

SYNTIA 5W30 SL/CF (LGO)

SYNTIA ULTIM 5W30 SL is a high performance synthetic motor oil of the latest generation for gasoline and diesel engines with turbocharging. The use of special selected additives provides an excellent cleanliness of the motor and protects the exhaust catalyst. Because of the high fluidity, an important fuel economy can be achieved. The excellent fluidity at low temperature results in a very low resistance when starting the engine, hereby reducing wear to a minimum. This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.

SYNTIA ULTIM 5W30 SL meets the following specifications:

ACEA: A1/B1/A5/B5-12

API: SL/CF

ADVANTAGES :

A universal high performance fuel economy motor oil special composed recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

FEATURES:

Total engine protection: outstanding engine cleanliness and durability.
Cold start: excellent fluidity at low temperature.
Fuel economy: lower fuel consumption and CO2 emissions.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
SAE-classe			5W30
Density at 15°C	D4052	kg/m3	0,856
Viscosity at 40°C	D445	cSt	66
Viscosity at 100°C	D445	cSt	11.1
Viscosity at -30°C	D5293	cP	6285
Viscosity index	D2270		164
Flash point COC	D92	°C	230
Pour point	D6892	°C	-33
TBN	D2896	gKOH/kg	8.1
Sulphated ash	D874	massa %	1,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: **ARV 117**