

SYNTULA 0W30 LL CET

SYNTULA 0W30 LL CET A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalyts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

This oil can be used in all WIV-vehicles, except in AUDI S3, RS4, Audi TT with 225 hp, W-engines, specifically developed to meet the "long life" requirements of Volkswagen and Audi cars

SYNTULA 0W30 LL CET meets the following specifications:

- ACEA C3-12
- Meets the requirements of
- VW 504.00/507.00
- VW: 503 00
- VW: 506 00
- VW: 506 01

FEATURES

Total engine protection : performance in keeping the engine clean.

Fuel economy : superior fuel economy and CO2 reduction.

Cold start : excellent fluidity at low temperature.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W30
Density at 15°C	D4052	kg/m3	844
Viscosity at 40°C	D445	cSt	55.3
Viscosity at 100°C	D445	cSt	10.1
Viscosity index	D2270		174
Flash point COC	D92	°C	220
Pour point	D6892	°C	-51
TBN	D2896	gKOH/kg	10.2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.

Product code: ARV139