

## SYNTULA 0W30 V

**SYNTULA 0W30 V** This is a full synthetic lubricant based on carefully selected very high quality base oils that was especially developed to meet the requirements of Volvo passenger cars. It is characterized by increased lubricating properties and a better fuel economy. In this way it procures a reduced fuel consumption and a longer lifetime of the engine.

**SYNTULA 0W30 V** meets the following specifications:

API SL/ CF  
ACEA: A5/B5-12  
VOLVO: VCC 95200377

### APPLICATIONS :

This oil is recommended for the gasoline and diesel models of Volvo Cars of the latest generations, equipped with 5-cylinder engines.

### FEATURES

Cold start : very good fluidity at low temperature.  
Total engine protection : performance in keeping the engine clean.  
Fuel economy : superior fuel economy and CO2 reduction.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W30
Density at 15°C	D4052	kg/m <sup>3</sup>	850
Viscosity at 40°C	D445	cSt	54.9
Viscosity at 100°C	D445	cSt	10.3
Viscosity at -35°C	D5293	cP	6000
Viscosity index	D2270		178
Flash point COC	D92	°C	221
Pour point	D6892	°C	-45
TBN	D2896	gKOH/kg	10

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.*

Product code: ARV 116