

## SYNTIA ULTIM 5W40 SN

**SYNTIA ULTIM 5W40** is a high performance engine oil of the latest generation, specially designed to meet the strict requirements of manufacturers and composed of non-conventional base oils and high quality additives.

**SYNTIA ULTIM 5W40** meets the following performance criteria:

API SN/CF  
ACEA A3/B3/B4-08  
VW 502.00/505.00  
MB 229.3 – MB 226.5  
Porsche A40  
PSA B71 2296  
Renault RN 0700- RN 0710  
BMW Longlife-01  
Opel GM-LL-B-25

### ADVANTAGES :

A universal, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

### TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
Density @15°C	ASTM D4052	kg/l	0,857
Viscosity @-30°C		mPa.s	6140
Viscosity @40°C	ASTM D7042	mm <sup>2</sup> /s	85,80
Viscosity @100°C	ASTM D7042	mm <sup>2</sup> /s	14,00
Viscosity Index	ASTM D2270		173
Flash point COC	ASTM D92	°C	223
Pour point	ASTM D97	°C	-39
Total Base Nummer	ASTM D2896	mgKOH/g	9,7
Sulphated Ash	ASTM D874	%	1,22

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

Product code: **ARVA111**