

SYNTULA ECO H 0W20

SYNTULA ECO H 0W20 is high performance fuel saving engine oil based on 100% synthetic technology for all gasoline engines in passenger car and light vans.

SYNTULA ECO H 0W20 is specially designed for the lubricating the latest generation vehicles like hybrid and ECO models which require a SAE 0W-20.

SYNTULA ECO H 0W20 is based on synthetic base oil in combination with a special additive package to obtain the following properties:

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for a smooth cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties.
- Very good antifoam, anti-wear and anti-corrosion properties.
- LOW SAPS technology, suitable for engines equipped with exhaust gas after treatment like DPF
- Long oil change interval possible.

SYNTULA ECO H 0W20 meets the following performance criteria:

- API SP Resource Conserving
- ILSAC GF 6A
- GM dexos 1 Gen 2.
- GM 4718M
- Chrysler MS-6395
- FORD WSS-M2C945-A, WSS-M2C947-A/ WSS-M2C946-A
-

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
SAE-classe			0W20
Density at 15°C	D4052	kg/m ³	0,853
Viscosity at 40°C	D445	cSt	44
Viscosity at 100°C	D445	cSt	8,6
Viscosity at -30°C	D5293	cP	6600
Viscosity index	D2270		178
Flash point COC	D92	°C	> 222
Pour point	D6892	°C	-39
TBN	D2896	gKOH/kg	8
Sulphated ash	D874	massa %	0,87

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: **ARVA144**