

SYNTULA 0W30 PSA C2

SYNTULA 0W30 PSA C2 This is a This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines with exhaust after treatment and turbocharger. This specification demands high stability to ensure long oil drain intervals. It also addresses the use of biofuels. There is a fuel economy benefit over a 5W40 reference oil of 4,2%.

SYNTULA 0W30 PSA C2 meets the following specifications:

- ACEA: C2-12
- PSA: B71 2312
- FIAT: 9.55535-GS1
- FIAT: 9.55535-DS1

FEATURES

Total engine protection : performance in keeping the engine clean.

Fuel economy : superior fuel economy and CO2 reduction.

Cold start : excellent fluidity at low temperature.

APPLICATIONS :

This product was primarily developed for mandatory use in the PSA EURO VI Blue HDi DW10F engines and particularly ones equipped with e-HDi using Stop & Start technologies. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's cars with extended service intervals

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W30
Density at 15°C	D4052	kg/m ³	842
Viscosity at 40°C	D445	cSt	55
Viscosity at 100°C	D445	cSt	9.8
CCS Viscosity at -25°C	D5293	cP	5920
Viscosity index	D2270		171
Flash point COC	D92	°C	230
Pour point	D6892	°C	-48
TBN	D2896	gKOH/kg	6.2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.

Product code: ARV137