

SYNTULA 5W30 LL III CET

FULL SYNTHETIC <<LONGLIFE>> CLEAN EMISSION TECHNOLOGIE CET.

SYNTULA 5W30 CET LL III is a 100% synthetic, fuel economy "low SAPS" motor oil of the latest generation, which is especially developed to meet the "long life III" requirements of the cars of the constructors Volkswagen, Audi, Skoda and Seat. It is a Mid SAPS oil which meets Euro 4 and Euro 5 and 6 norms and provides protection to the Diesel Particulate Filter. It is particularly designed for downsized Turbocharged Gasoline Direct Injection (TGDI) engines to mitigate LSPI (Low Speed Pre Ignition).

SYNTULA 5W30 LL III CET meets the following specifications:

- ACEA A3/B4, C2*, C3-10
- API SN plus / API SP
- MB 229.31/ 229.51 / 229.52
- VW 504.00/507.00
- BMW LL-04
- PORSCHE C30
- Opel OV0401547

APPLICATIONS:

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01). All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 onwards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification. Meets all engine protection requirements of ACEA C2*.

TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
SAE-classe			5W30
Density at 15°C	D4052	kg/m ³	849
Viscosity at 40°C	D445	cSt	70
Viscosity at 100°C	D445	cSt	11,6
Viscosity at -20°C	D5293	cP	5800
Viscosity index	D2270		159
Flash point COC	D92	°C	230
Pour point	D6892	°C	-39
TBN	D2896	gKOH/kg	6,0
Sulphated ash	D874	massa %	0,7

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV100