

## SYNTULA 5W30 GM DEX1 Gen.2

**SYNTULA 5W30 GM DEX1 gen. 2** is a full synthetic fuel economy motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- outstanding engine cleanliness and durability.
- High and very stable viscosity index
- lower fuel consumption and CO2 emissions.
- A fast cold start excellent fluidity at low temperature.

**SYNTULA 5W30 GM DEX1 gen. 2** meets the following specifications:

API SN/RC  
 CHRYSLER: MS 6395  
 FORD: WSS-M2C945-A  
 FORD: WSS-M2C946-A  
 FORD: WSS-M2C947-A  
 GM: dexos1™ Gen 2  
 ILSAC: GF-5

**RC = Resource Conserving** ( *API SN + Resource Conserving = ILSAC GF-5* )

- Emission system protection
- Turbocharger protection
- Compatibility with engines operating on ethanol containing fuels, up to E-85

### APPLICATIONS :

This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters, DPF.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D4052	kg/l	0,852
Viscosity at 40°C	D445	mm <sup>2</sup> /s	60.1
Viscosity at 100°C	D445	mm <sup>2</sup> /s	10.3
Viscosity index	D2270		159
Flash point COC	D92	°C	221
Pour point	D6892	°C	-45
Sulfated ash	D874	massa %	0,94

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

Product code: ARV140