

SYNTULA ECO F 0W30

SYNTULA ECO F 0W30 is a fully synthetic engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Due to its very low viscosity, immediate lubrication after starting is obtained, together with a high level of fuel economy and low saps requirements

SYNTULA ECO F 0W30 meets the following specifications:

API SN/ CF
ACEA A3/ B4-12
BMW LONG LIFE 01
MB: 229.3-226.5
VW: 502 00
VW: 505 00
RN: RN0700

APPLICATIONS :

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters. This product is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W30
Density at 15°C	D4052	kg/m ³	854
Viscosity at 40°C	D445	cSt	51.1
Viscosity at 100°C	D445	cSt	11
Viscosity at -35°C	D5293	cP	5930
Viscosity index	D2270		181
Flash point COC	D92	°C	230
Pour point	D6892	°C	-45
TBN	D2896	gKOH/kg	10.5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.

Product code: ARV114