

SYNTULA ECO FS 0W20

SYNTULA ECO FS 0W20 is a fully synthetic engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Due to its very low viscosity, immediate lubrication after starting is obtained, together with a high level of fuel economy.

SYNTULA ECO FS 0W20 meets the following specifications:

- API SN/ RC
- ACEA A1/B1-10
- ILSAC GF-5
- Chrysler:MS6395
- Ford: M2C945-A / M2C947-A

APPLICATIONS :

This product has been specifically developed to meet the challenging requirements for Hybrid cars where fuel economy and co2 reduction is important.

It provides the performance needed for the most recent requirements for gasoline-fueled Us and Asian (i.e. Honda, Toyota, Mitsubishi) passenger cars.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W20
Density at 15°C	D4052	kg/m3	849
Viscosity at 40°C	D445	cSt	45,4
Viscosity at 100°C	D445	cSt	8,51
Viscosity at -35°C	D5293	cP	6180
Viscosity index	D2270		173
Flash point COC	D92	°C	220
Pour point	D6892	°C	-51
TBN	D2896	gKOH/kg	8,2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV119