

## SYNTULA BM 0W30

**SYNTULA BM 0W30** This is a full synthetic lubricant based on carefully selected very high quality base oils that was especially developed to meet the requirements of BMW LONF LIFE 12 FE specifications. It is characterized by increased lubricating properties and a better fuel economy. In this way it procures a reduced fuel consumption and a longer lifetime of the engine. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

**SYNTULA BM 0W30** meets the following specifications:

ACEA: C2-12

**BMW: Long LIFE 12 FE**

### APPLICATIONS :

This product is used for the newest BMW gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

### FEATURES

Cold start : very good fluidity at low temperature.

Total engine protection : performance in keeping the engine clean.

Fuel economy : superior fuel economy and CO2 reduction.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W30
Density at 15°C	D4052	kg/m <sup>3</sup>	841
Viscosity at 40°C	D445	cSt	54.9
Viscosity at 100°C	D445	cSt	9.8
Viscosity at -35°C	D5293	mPas	5400
Viscosity index	D2270		170
Flash point COC	D92	°C	225
Pour point	D6892	°C	-57
TBN	D2896	gKOH/kg	10

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.*

Product code: ARV 134

