

RACING PRO 10W60

FULLY SYNTHETIC RACING MOTOR OIL.

RACING PRO 10W60 is a fully synthetic engine oil of the latest generation, for the lubrication of all high performance engines.

RACING PRO 10W60 meets the following specifications:

ACEA: A3/B4-08

API: SN/CF

BMW: LONGLIFE-01

BMW: M-MODELS

MB: 229.3

VW: 501 01

VW: 505 00

APPLICATIONS :

4-stroke gasoline engines, multi-valves, turbo and diesel engines 4T, with or without turbo.

ADVANTAGES :

Excellent fluidity at low temperature.

Very low resistance at start.

Exceptional viscosity index.

Very high thermal stability.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W60
Density at 15°C	D4052	kg/m ³	871
Viscosity at 40°C	D445	cSt	171
Viscosity at 100°C	D445	cSt	24,5
Viscosity at -30°C		cP	6700
Viscosity index	D2270		175
Flash point COC	D92	°C	238
Pour point	D6892	°C	-36
TBN	D2896	gKOH/kg	9,5
Sulphated ash	D874	massa %	1,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV125